

1 Identification

- **Product identifier**
- **Trade name:** Resin solution X 50
- **Article number:** 1234567890
- **Application of the substance / the mixture** Raw material for resins
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Chemix GmbH
 Chemixstraße 17
 A-5020 Salzburg Tel.: 0043/662/21 22 23
- **Information department:** Product safety department
- **Emergency telephone number:**
 CHEMTREC 24-Hour Emergency Telephone Number: (800)424-9300
 CHEMTREC 24-Hour Emergency Telephone Number (Outside of the U.S. and Canada): (703)527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids - Category 3	H226	Flammable liquid and vapour.
Skin Irritation - Category 2	H315	Causes skin irritation.
Eye Irritation - Category 2A	H319	Causes serious eye irritation.
Skin Sensitizer - Category 1	H317	May cause an allergic skin reaction.
Reproductive Toxicity - Category 2	H361-H362	Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation. May cause harm to breast-fed children.
Specific Target Organ Toxicity - Single Exposure - Category 3	H336	May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure - Category 2	H373	May cause damage to the digestive system through prolonged or repeated exposure. Route of exposure: Dermal.
Aspiration Hazard - Category 1	H304	May be fatal if swallowed and enters airways.

- **Label elements**
- **GHS label elements**
 The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
 toluene
 ethyl acetate
 butanol
 propan-2-ol
- **Hazard statements**
 Flammable liquid and vapour.
 Causes skin irritation.
 Causes serious eye irritation.

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 1)

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation. May cause harm to breast-fed children.

May cause drowsiness or dizziness.

May cause damage to the digestive system through prolonged or repeated exposure. Route of exposure: Dermal.

May be fatal if swallowed and enters airways.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Avoid contact during pregnancy and while nursing.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take actions to prevent static discharges.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

Hazard description:

WHMIS-symbols:

B2 - Flammable liquid

D2A - Very toxic material causing other toxic effects



Classification system:

NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ⚠ Skin Irritation - Category 2, H315; Eye Irritation - Category 2, H319; Skin Sensitizer - Category 1, H317	25-90% w/w
108-88-3	toluene ⚠ Flammable Liquids - Category 2, H225; ⚠ Reproductive Toxicity - Category 2, H361; Specific Target Organ Toxicity - Repeated Exposure - Category 2, H373; Aspiration Hazard - Category 1, H304; ⚠ Skin Irritation - Category 2, H315; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	20-<25% w/w
141-78-6	ethyl acetate ⚠ Flammable Liquids - Category 2, H225; ⚠ Eye Irritation - Category 2, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	20-<25% w/w
78-92-2	butanol ⚠ Flammable Liquids - Category 3, H226; ⚠ Eye Irritation - Category 2, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H335-H336	0.1-<10% w/w
67-63-0	propan-2-ol ⚠ Flammable Liquids - Category 2, H225; ⚠ Eye Irritation - Category 2, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	0.1-<10% w/w

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Sand. Do not use water.
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

108-88-3 toluene

EL Long-term value: 20 ppm
R

EV Long-term value: 20 ppm

141-78-6 ethyl acetate

EL Long-term value: 150 ppm

EV Long-term value: 1.440 mg/m³, 400 ppm

78-92-2 butanol

EL Long-term value: 100 ppm

EV Short-term value: 150 ppm
Long-term value: 100 ppm

67-63-0 propan-2-ol

EL Short-term value: 400 ppm
Long-term value: 200 ppm

EV Short-term value: 400 ppm
Long-term value: 200 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Liquid
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	77 °C

· Flash point: 26 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 390 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:	1.2 Vol %
· Upper:	11.5 Vol %

· Vapor pressure at 20 °C: 97 hPa

· Density: Not determined.

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

· Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· Solvent content:

· Organic solvents: 50.0 %

· Solids content: 50.0 %

· Other information: No further relevant information available.

CA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 6)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

Oral	LD50	25000 mg/kg (rat)
Inhalation	LC50/4 h	558 mg/l (rat)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalation	LC50/4 h	5320 mg/l (mouse)

141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalation	LC50/4 h	1600 mg/l (rat)

78-92-2 butanol

Oral	LD50	6480 mg/kg (rat)
------	------	------------------

67-63-0 propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalation	LC50/4 h	30 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
67-63-0	propan-2-ol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

CA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 7)




12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, TDG, IMDG, IATA | <p style="margin: 0;">UN1866</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · TDG · IMDG, IATA | <p style="margin: 0;">Resin solution</p> <p style="margin: 0;">Resin solution, special provision 640E, ENVIRONMENTALLY HAZARDOUS</p> <p style="margin: 0;">RESIN SOLUTION</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> <p style="margin: 10px 0 0 20px;">3 Flammable liquids</p> |
| <ul style="list-style-type: none"> · Class · Label · TDG (Transport dangerous goods): | <p style="margin: 0;">3</p> |
| <ul style="list-style-type: none"> · Class | <div style="text-align: center;">   </div> <p style="margin: 10px 0 0 20px;">3 Flammable liquids</p> |

(Contd. on page 9)

CA

Safety Data Sheet

acc. to OSHA HCS


Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 8)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, TDG, IMDG, IATA	III
· Environmental hazards:	Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
· Special marking (TDG):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· TDG	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, SPECIAL PROVISION 640E, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene

78-92-2 butanol

67-63-0 propan-2-ol

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 10)

CA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 9)

· Chemicals known to cause reproductive toxicity for females:	
108-88-3	toluene

· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	

· Chemicals known to cause developmental toxicity:	
108-88-3	toluene

· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
108-88-3	toluene	II




· TLV (Threshold Limit Value established by ACGIH)		
108-88-3	toluene	A4
67-63-0	propan-2-ol	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· Canadian substance listings:	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	

· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	

· Canadian Ingredient Disclosure list (limit 1%)	
108-88-3	toluene
141-78-6	ethyl acetate
78-92-2	butanol
67-63-0	propan-2-ol

· GHS label elements		
The product is classified and labeled according to the Globally Harmonized System (GHS).		
· Hazard pictograms		
		
GHS02	GHS07	GHS08
· Signal word Danger		
· Hazard-determining components of labeling:		
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
toluene		
ethyl acetate		
butanol		
propan-2-ol		
· Hazard statements		
Flammable liquid and vapour.		
Causes skin irritation.		
Causes serious eye irritation.		
May cause an allergic skin reaction.		
Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation. May cause harm to breast-fed children.		
May cause drowsiness or dizziness.		
May cause damage to the digestive system through prolonged or repeated exposure. Route of exposure: Dermal.		
May be fatal if swallowed and enters airways.		



(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 10)

· **Precautionary statements**

- If medical advice is needed, have product container or label at hand.*
Keep out of reach of children.
Read label before use.
Avoid contact during pregnancy and while nursing.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use explosion-proof [electrical/ventilating/lighting] equipment.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
Ground and bond container and receiving equipment.
Use non-sparking tools.
Take actions to prevent static discharges.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Do not handle until all safety precautions have been read and understood.
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Do NOT induce vomiting.
In case of fire: Use for extinction: CO2, powder or water spray.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** Environment protection department.
 · **Contact:** Dr. Peter Mayer
 · **Date of preparation / last revision** 09/11/2015 / 2.9
 · **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flammable Liquids - Category 2: Flammable liquids, Hazard Category 2
Flammable Liquids - Category 3: Flammable liquids, Hazard Category 3

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2015

Version 3.0

Reviewed on 09/11/2015

Trade name: Resin solution X 50

(Contd. of page 11)

*Skin Irritation - Category 2: Skin corrosion/irritation, Hazard Category 2**Eye Irritation - Category 2: Serious eye damage/eye irritation, Hazard Category 2**Eye Irritation - Category 2A: Serious eye damage/eye irritation, Hazard Category 2A**Skin Sensitizer - Category 1: Sensitisation - Skin, Hazard Category 1**Reproductive Toxicity - Category 2: Reproductive toxicity, Hazard Category 2**Specific Target Organ Toxicity - Single Exposure - Category 3: Specific target organ toxicity - Single exposure, Hazard Category 3**Specific Target Organ Toxicity - Repeated Exposure - Category 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2**Aspiration Hazard - Category 1: Aspiration hazard, Hazard Category 1**** Data compared to the previous version altered.**

CA