

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

- **Product identifier**
- **Trade name:** *Resin solution X 150*
- **Article number:** 1001.5679
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Raw material for resins*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Chemix GmbH
Chemixstraße 17
A-5020 Salzburg*
- Tel.: 0043/662/21 22 23
- **Further information obtainable from:** *Product safety department.*

2 Hazard(s) Identification

- **Classification of the substance or mixture**



flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



health hazard

Repr. 1A

H360 May damage fertility or the unborn child.

STOT RE 2

H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2

H315 Causes skin irritation.

Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

STOT SE 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
toluene

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Trade name: *Resin solution X 150*

(Contd. of page 1)

- **Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) <i>Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; Skin Sens. 1, H317</i>	30-60%
108-88-3	toluene <i>Flam. Liq. 2, H225; Repr. 1A, H360; STOT RE 2, H373; Skin Irrit. 2, H315</i>	10-<30%
141-78-6	ethyl acetate <i>Flam. Liq. 2, H225; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336</i>	≥ 20 -<30%
67-63-0	propan-2-ol <i>Flam. Liq. 2, H225; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336</i>	<10%
78-92-2	butanol <i>Flam. Liq. 3, H226; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H335-H336</i>	<10%
7440-02-0	nickel <i>Carc. 2, H351; STOT RE 1, H372; Skin Sens. 1, H317</i>	≥ 0.1 -<1%
80-05-7	bisphenol A <i>Repr. 2, H361; Eye Dam. 1, H318; Skin Sens. 1, H317; STOT SE 3, H335</i>	≥ 0.1 -<1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

AU

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Trade name: *Resin solution X 150*

(Contd. of page 2)

4 First Aid Measures

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** *If symptoms persist consult doctor.*

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

- **Protective equipment:** *Mouth respiratory protective device.*

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** *No special requirements.*

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Trade name: *Resin solution X 150*

(Contd. of page 3)

- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep container tightly sealed.*
- **Specific end use(s)** *No further relevant information available.*

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** *No further data; see item 7.*

- **Ingredients with limit values that require monitoring at the workplace:**

108-88-3 toluene

WES	Short-term value: 574 mg/m ³ , 150 ppm
	Long-term value: 191 mg/m ³ , 50 ppm
	Sk

141-78-6 ethyl acetate

WES	Short-term value: 1440 mg/m ³ , 400 ppm
	Long-term value: 720 mg/m ³ , 200 ppm

67-63-0 propan-2-ol

WES	Short-term value: 1230 mg/m ³ , 500 ppm
	Long-term value: 983 mg/m ³ , 400 ppm

78-92-2 butanol

WES	Long-term value: 303 mg/m ³ , 100 ppm
-----	--

7440-02-0 nickel

WES	Long-term value: 1 mg/m ³
	Metal: Sen

- **Additional information:** *The lists valid during the making were used as basis.*

- **Personal protective equipment:**

- **General protective and hygienic measures:**

*Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.*

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Trade name: *Resin solution X 150*

(Contd. of page 4)

· Eye protection:

*Tightly sealed goggles*

9 Physical and Chemical Properties

· General Information

· Appearance:

· Form:	<i>Fluid</i>
· Colour:	<i>According to product specification</i>
· Odour:	<i>Characteristic</i>
· Odour threshold:	<i>Not determined.</i>
· pH-value:	<i>Not determined.</i>
· Change in condition	
· Melting point/freezing point:	<i>Undetermined.</i>
· Initial boiling point and boiling range:	<i>77-78 °C</i>
· Flash point:	<i>25 °C</i>
· Flammability (solid, gas):	<i>Flammable.</i>
· Ignition temperature:	<i>390 °C</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto-ignition temperature:	<i>Product is not selfigniting.</i>
· Explosive properties:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
· Explosion limits:	
· Lower:	<i>1.2 Vol %</i>
· Upper:	<i>11.5 Vol %</i>
· Vapour pressure at 20 °C:	<i>97 hPa</i>
· Density:	<i>Not determined.</i>
· Relative density	<i>Not determined.</i>
· Vapour density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with	
· water:	<i>Not miscible or difficult to mix.</i>
· Partition coefficient: n-octanol/water:	<i>Not determined.</i>
· Viscosity:	
· Dynamic:	<i>Not determined.</i>
· Kinematic:	<i>Not determined.</i>
· Solvent content:	
· Organic solvents:	<i>49.0 %</i>
· VOC (EC)	<i>49.00 %</i>
· Solids content:	<i>50.0 %</i>

· Other information *No further relevant information available.*

10 Stability and Reactivity

- Reactivity *No further relevant information available.*
- Thermal decomposition / conditions to be avoided: *No decomposition if used according to specifications.*
- Possibility of hazardous reactions *No dangerous reactions known.*
- Conditions to avoid *No further relevant information available.*
- Incompatible materials: *No further relevant information available.*

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Trade name: *Resin solution X 150*

(Contd. of page 5)

· **Hazardous decomposition products:** *No dangerous decomposition products known.*

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** *Based on available data, the classification criteria are not met.*

- **LD/LC50 values relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

141-78-6 ethyl acetate

Oral	LD50	5,620 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (rat)

67-63-0 propan-2-ol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

78-92-2 butanol

Oral	LD50	6,480 mg/kg (rat)
------	------	-------------------

80-05-7 bisphenol A

Oral	LD50	3,250 mg/kg (rat)
Dermal	LD50	3,000 mg/kg (rabbit)

- **Skin corrosion/irritation** *Causes skin irritation.*
- **Serious eye damage/irritation** *Causes serious eye irritation.*
- **Respiratory or skin sensitisation** *May cause an allergic skin reaction.*
- **Germ cell mutagenicity** *Based on available data, the classification criteria are not met.*
- **Carcinogenicity** *Based on available data, the classification criteria are not met.*
- **Reproductive toxicity** *May damage fertility or the unborn child.*
- **STOT-single exposure** *May cause drowsiness or dizziness.*
- **STOT-repeated exposure** *May cause damage to organs through prolonged or repeated exposure.*
- **Aspiration hazard** *Based on available data, the classification criteria are not met.*

12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **Persistence and degradability** *No further relevant information available.*
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** *No further relevant information available.*
- **Mobility in soil** *No further relevant information available.*
- **Additional ecological information:**
- **General notes:**
*Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **Other adverse effects** *No further relevant information available.*

AU

(Contd. on page 7)

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022




Trade name: *Resin solution X 150*

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

<ul style="list-style-type: none"> · UN-Number · ADG, IMDG, IATA 	UN1993
<ul style="list-style-type: none"> · UN proper shipping name · ADG · IMDG · IATA 	FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, TOLUENE), ENVIRONMENTALLY HAZARDOUS FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, TOLUENE), MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, TOLUENE)
<ul style="list-style-type: none"> · Transport hazard class(es) · ADG, IMDG 	<div style="display: flex; align-items: center; gap: 10px;">   </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · IATA 	<div style="display: flex; align-items: center; gap: 10px;">  </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · Packing group · ADG, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: · Special marking (ADG): 	Product contains environmentally hazardous substances: 2-methyl-2H-isothiazol-3-one Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.

(Contd. on page 8)

AU

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Trade name: *Resin solution X 150*

(Contd. of page 7)

· **Transport/Additional information:**

· **ADG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, TOLUENE), 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Australian Inventory of Industrial Chemicals**

All ingredients are listed.

· **Standard for the Uniform Scheduling of Medicines and Poisons**

108-88-3	toluene	S6
2682-20-4	2-methyl-2H-isothiazol-3-one	S6

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **Chemical safety assessment:** *A Chemical Safety Assessment has been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** *Product safety department.*

· **Contact:** *Dr. Peter Mayer*

(Contd. on page 9)

Safety Data Sheet

according to WHS Regulations

Printing date 21.12.2022

Version number 2.0

Revision: 19.12.2022

Trade name: Resin solution X 150

(Contd. of page 8)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Repr. 1A: Reproductive toxicity – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

*** Data compared to the previous version altered.**

AU